ER25-1800

ER25-1800,

Maxium payload 25 kg with maxium reach 1850 mm.

Highlights

Thanks to the new design of wrist, inertia and bearing capacity are increased by 25% with wider application scope;

EFORT

Thanks to the high stiffness transmission design and advanced trajectory algorithm, the improved robot accuracy performance helps customers to face variety of application scenarios; Lighter weight of the body, 20% less than its predecessor.

Applications

It can be used in handling operations, assembling, grinding, polishing, deburring, etc.

Industries


Suitable for metal parts, photovoltaic, logistics, food and beverage and other industries.

EFORT


SPECIFICATIONS

Model		ER25-1800
Туре		Articulated
Controlled axes		6 Axes
Max. payload on wrist		25 kg
Repeatability		±0.05 mm
Robot weight		175 kg
Reach		1850 mm
Robot IP grade		IP54 / IP67 (Wrist)
Cabinet IP grade		IP20 / IP54 (Optional)
Drive mode		AC servo drive
Installation		Floor, Upside-down, Wall
	Ambient temperature	0~45 °C
Installation enviroment	Ambient humidity	RH≤80%(No dew nor frost allowed)
	Vibration acceleration	4.9 m/s ² (<0.5 G)

OPERATING SPACE



BASE MOUNTING SIZE



EFORT Intelligent Equipment Co., Ltd.

PHONE: (00 86) 400-052-8877 ADDRESS: No.96 East Wanchun Road, China(Anhui) Pilot Free Trade Zone Wuhu Area, Wuhu, Anhui Province, China WWW.EFORT.COM.CN

Allowable load moment at wrist	J 4	50 N•m
	J 5	50 N•m
	J 6	30 N•m
Allowable load inertia at wrist	J 4	2.2 kg•m²
	J 5	2.2 kg•m²
	J 6	1.5 kg·m²
	J1	220°/sec
	J 2	180°/sec
Maximum spaced	J 3	200%sec
Maximum speed	J 4	360°/sec
	J 5	360°/sec
	J6	410°/sec
	J1	±170°
	J 2	+77°/-160°
Mation rouge	J 3	+165°/-85°
Motion range	J 4	±190°
	J 5	±130°
	J 6	±360°

