ER50-2100



ER50-2100,

Maxium payload 50 kg with maxium reach 2146 mm.

■ Highlights

Thanks to the high stiffness structure, with high-speed intelligent palletizing application software, the takt is improved by 20%, bring customers more efficiency:

Multiple specific application software could be integrated, with soft PLC and a variety of field bus interface, which enable customers easily face various application challenges;

High performance collision detection function helps safety realization.

Applications

It can be used in grinding, polishing, handling operations, palletizing, etc.

Industries

Suitable for auto parts, photovoltaic, food and beverage, building materials, logistics and warehousing and other industries.



EFORT Intelligent Equipment Co., Ltd.

PHONE: (00 86) 400-052-8877


ADDRESS: No.96 East Wanchun Road, China(Anhui) Pilot Free Trade Zone Wuhu Area, Wuhu, Anhui Province, China WWW.EFORT.COM.CN

SPECIFICATIONS


Model		ER50-2100
Туре		Articulated
Controlled axes		6 Axes
Max. payload on wrist		50 kg
Repeatability		±0.06 mm
Robot weight		550 kg
Reach		2146 mm
Robot IP grade		IP54/IP67 (Wrist)
Cabinet IP grade		IP54
Drive mode		AC servo drive
Installation		Floor
	Ambient temperature	0~45 °C
Installation enviroment	Ambient humidity	RH≤80% (No dew nor frost allowed)
	Vibration acceleration	4.9 m/s ² (<0.5 G)

Allowable load moment at wrist	J 4	182 N·m
	J 5	182 N·m
	J6	120 N·m
Allowable load inertia at wrist	J 4	12.68 kg·m²
	J 5	12.68 kg·m²
	J6	10 kg·m²
	J1	170°/sec
	J2	170°/sec
Maximum speed	J3	170°/sec
Maxilliulli speeu	J 4	270°/sec
	J 5	270°/sec
	J6	365°/sec
	J1	±180°
	J2	+70°/-130°
Metien venge	13	+175°/-80°
Motion range	J 4	±360°
	J 5	±115°
	J6	±450°
		-


OPERATING SPACE



BASE MOUNTING SIZE



END FLANGE MOUNTING SIZE



Information Release Time 2024/12